

auxiliary contact, TransferPacT, indication for source I and souce II, frame 250A, frame 630A

TPSAUX43

Main

Range of product	TransferPacT
Product or component type	Auxiliary Contact Module
Device application	Signalling

Complementary

Auxiliary contact composition	2 NO + 2 NC
Signalling function	Switch position (SI and SII)
Auxiliary connection terminal	Spring 0.51.5 mm² (AWG 20AWG 16)
mounting mode	Clip-on
mounting position	Inside front cover
[Ith] conventional free air thermal current	5 A
Minimum load	100 mA at 24 V DC
Tightening torque	0.6 N.m +/- 0.1 N.m
Product compatibility	TA25 TR25 TA63 TR63
Accessory / separate part category	Signalling accessory

Environment

IP degree of protection	IP20	
Pollution degree	3	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.500 cm
Package 1 Width	7.000 cm
Package 1 Length	7.500 cm
Package 1 Weight	34.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.000 cm

Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	634.000 g

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Well-being performance



Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information