# **Product datasheet**

Specifications





## Double socket-outlet, Unica Pure, 2P + E, 6/16A, 2 modules, polar white

UNS616SK2M\_WE

#### Main

Range	Unica Pure
Product or component type	Socket-outlet
device presentation	Mechanism
Number of modules	2 modules
Socket number	2
Colour tint	White (RAL 9003)

## Complementary

Device mounting	Flush
Outlet poles configuration	2P + E
Rated current	6/16 A
[Ue] rated operational voltage	240 V
network type	AC
network frequency	50 Hz
Material	PC front cover PA6 back cover
Width	45 mm
Height	45 mm
Depth	32 mm

#### Environment

Ambient air temperature for operation	-535 °C
Relative humidity	1095 %
Standards	IS 1293
IP degree of protection	IP20

## **Packing Units**

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.2 cm
Package 1 Width	6.6 cm
Package 1 Length	9 cm

Package 1 Weight	40 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	5.9 cm
Package 2 Width	10.4 cm
Package 2 Length	23.2 cm
Package 2 Weight	360 g

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations