Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product datasheet





Buzzer, Unica pure, 70dB, 1 module, IP41, white

UNSBUZZER1M_WE

Main

Range	Unica Pure
Product or component type	Buzzer
device presentation	Mechanism
[Ue] rated operational voltage	220 V
Number of modules	1 module
Fixing mode	Snap-in
Colour tint	White
Main colour tint	White

Complementary

Device mounting	Flush	
Operating time	60 s	
Noise level	70 dB	
Cable cross section	1.52.5 mm² flexible cable 1.52.5 mm² rigid or stranded cable	
Material	ABS (acrylonitrile butadiene-styrene): front cover PC (polycarbonate) GF10 FR: back cover	
Standards	IEC 62080	
Ambient air temperature for operation	-535 °C	
Depth	53 mm	
Width	22.5 mm	
Height	45 mm	
Net weight	0.037 kg	

Environment

IK degree of protection	IK04	
IP degree of protection	IP41	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	13 cm

Package 1 Length	13 cm	
Package 1 Weight	45 a	



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations