Product datasheet

Specifications





Switch, Unica Pure, 1-pole 1-way, 6AX, 1 module, pillar terminals, grey

UNS61SW1M_GY

Main

Range	Unica Pure	
Product or component type	Switch	
device presentation	Mechanism	
Technology type	Electromechanical	
Colour tint	Grey (RAL 7016)	

Complementary

Device mounting	Flush	
Number of rocker	1	
Number of modules	1 module	
Control type	Rocker	
Switch function	1-pole 1-way	
Rated current	6 AX	
[Ue] rated operational voltage	240 V	
network type	AC	
network frequency	50 Hz	
Material	PC: front cover PA6: back cover	
Connections - terminals	Pillar terminals	
Width	22.5 mm	
Height	45 mm	
Depth	47.2 mm	

Environment

Ambient air temperature for operation	-535 °C
Relative humidity	1095 %
Environmental characteristic	Indoor use
Standards	IS 3854
IP degree of protection	IP20

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1	1
Package 1 Height	9 cm
Package 1 Width	12 cm
Package 1 Length	25.6 cm
Package 1 Weight	24 g
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	10.5 cm
Package 2 Width	7.5 cm
Package 2 Length	24 cm
Package 2 Weight	480 g



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations