Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product datasheet

Specifications





Opale dimmer 400W white

X3004WH

Main

Range	Opale	
Product or component type	Dimmer	
Device application	Control	
Dimmer type	Rotary dimmer	
Load type	Incandescent lamp	
Colour tint	White	
Main colour tint	White	
Material	PC: front cover PA (polyamide) 6: base cover PC: knob	
[Ue] rated operational voltage	220 V	
network type	AC	
network frequency	50/60 Hz	

Complementary

Device mounting	Flush	
dimmer control	Rotary	
number of modules	2	
Power range	400 W	
Surface finish	Satin	
Fixing mode	By captive screws	
Height	51 mm	
Width	42.25 mm	
Depth	62 mm	

Environment

IP degree of protection IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.4 cm
Package 1 Width	1.2 cm

Package 1 Length	4.7 cm
Package 1 Weight	50.2 g
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Height	7 cm
Package 2 Width	6 cm
Package 2 Length	23.5 cm
Package 2 Weight	332.25 g



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations