



TWIN RJ11 TELEPHONE O/L FOR NO SHITTER White

X4020WH

! Discontinued on: 30-Jun-2023

! Discontinued

Main

Range	Opale
Product or component type	Telephone socket
device presentation	Complete product
Cable shielding type	UTP
Data socket type	RJ11
Colour tint	White
Type of packing	Flow-pack
Quantity per set	10
Colour tint	White

Complementary

,			
Device mounting	Flush		
Socket number	2		
Communication network category	6		
Connections - terminals	IDC		
Cable stiffness	Rigid		
Material	ABS + PC: front cover PA6: base cover		
Fixing mode	Claws		
Height	48 mm		
Width	21 mm		
Depth	28 mm		
Environmental characteristic	Acetone Window-cleaning fluid Liquid soap Bleach Oil Alcohol		

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for storage	035 °C

Petrol

Ambient air temperature for	1530 °C
operation	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.5 cm
Package 1 Width	1 cm
Package 1 Length	1.2 cm
Package 1 Weight	14.8 a



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Sustainable Packaging Transparency RoHS/REACh

Resource performance



Sustainable Packaging

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Eu Rohs Directive

Compliant

EU RoHS Declaration

China Rohs Regulation

China RohS declaration

Pro-active China RohS declaration (out of China RohS legal scope)

Environmental Disclosure

Product Environmental Profile

Circularity Profile

No need of specific recycling operations