## **Product datasheet**

Specification





# pendant control station XAC-A - 5 pushbuttons 1 Emergency stop

XACA6913

#### Main

Range Of Product	Harmony XAC	
Product Or Component Type	Pendant control station	
Device Short Name	XACA	

#### Complementary

Complementary		
Control Station Type	Double insulated	
Enclosure Material	Polypropylene	
Electrical Circuit Type	Control circuit	
Enclosure Type	Complete ready for use	
Control Station Application	Control of 2-speed hoist motor	
Control Station Composition	7 push-buttons + 1 emergency stop	
Control Button Type	Emergency stop push-button Ø 40 mm 1 NC trigger action blank First push-button 1 NC + 1 NO + 1 NO raise, slow-fast Second push-button 1 NC + 1 NO + 1 NO lower, slow-fast Third push-button 1 NC + 1 NO + 1 NO left, slow-fast Fourth push-button 1 NC + 1 NO + 1 NO right, slow-fast Fifth push-button 1 NC + 1 NO + 1 NO forward, slow-fast	
Product Compatibility	ZB2BE102 for emergency stop ZB2BE102 + ZB2BE101 for each direction XENG1191	
Mechanical Interlocking	With mechanical interlocking between pairs	
Control Station Colour	Yellow	
Connections - Terminals	Screw clamp terminals, 1 x 0.51 x 2.5 mm² without cable end Screw clamp terminals, 1 x 0.52 x 1.5 mm² with cable end	
Standards	IEC 60947-5-1 IEC 60204-32 CSA C22.2 No 14 UL 508 IEC 60947-5-5 EN/ISO 13850: 2006	
Product Certifications	CCC GOST	
Protective Treatment	тн	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-4070 °C	
Vibration Resistance	15 gn (f= 10500 Hz) conforming to IEC 60068-2-6	
Shock Resistance	100 gn conforming to IEC 60068-2-27	

Ip Degree Of Protection	Degree Of Protection IP65 conforming to IEC 60529	
Ik Degree Of Protection	IK08 conforming to IEC 62262	
Mechanical Durability	1000000 cycles	
Cable Entry	Rubber sleeve with stepped entry 826 mm	
Contact Code Designation	A600 AC-15, Ue = 240 V, Ie = 3 A conforming to IEC 60947-5-1 appendix A A600 AC-15, Ue = 600 V, Ie = 1.2 A conforming to IEC 60947-5-1 appendix A Q600 DC-13, Ue = 250 V, Ie = 0.27 A conforming to IEC 60947-5-1 appendix A Q600 DC-13, Ue = 600 V, Ie = 0.1 A conforming to IEC 60947-5-1 appendix A	
the] Conventional Enclosed 10 A nermal Current		
[Ui] Rated Insulation Voltage	Emergency stop contact: 400 V (pollution degree 3) conforming to IEC 60947-1 600 V (pollution degree 3)	
[Uimp] Rated Impulse Withstand Voltage	Nithstand 6 kV conforming to IEC 60947-1	
Contact Operation	Slow-break	
Maximum Resistance Across Terminals	25 MOhm	
Operating Force	13 N push-button 14 N emergency stop	
Short-Circuit Protection	10 A fuse protection by cartridge fuse type gG	
Rated Operational Power In W	40 W DC-13 for 1000000 cycles, operating rate <60 cyc/mn at 120 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 48 W DC-13 for 1000000 cycles, operating rate <60 cyc/mn at 48 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 65 W DC-13 for 1000000 cycles, operating rate <60 cyc/mn at 24 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C	
Terminals Description Iso N°1	(13-14)NO (11-12)NC	
Terminals Description Iso N°2	(31-32)NC (11-12)NC (21-22)NC	
Terminal Identifier	(11-12)NC (13-14)NO	
Net Weight	0.97 kg	

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	11.0 cm
Package 1 Length	70.0 cm
Package 1 Weight	1.271 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	25
Package 2 Height	75.0 cm
Package 2 Width	80.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	39.775 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>Ø</b>	Reach Free Of Svhc	
<b>②</b>	Toxic Heavy Metal Free	
<b>Ø</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations