Product data sheet

Specifications





Drilled front plate, Harmony XAP, XB2 SL, metal, 1 cut out, 72x72mm, 22mm

XAPE301

Product availability: Stock - Normally stocked in distribution

Price*: 52.00 USD

Main

Range of Product	Harmony XAP			
Product or Component Type	Front plate with fixing screws			
Device short name	XAPE			
Product destination	For Ø 22 mm control and signalling units			
Product front plate size	72 x 72 mm			
Number of cut-out	1 cut-out			
Material	Anodised aluminium			
Device mounting	Flush			
IP degree of protection	IP65 IEC 60529 IP657 NF C 20-010			
Resistance to chemical agents	Good resistant to acetone Good resistant to alcohols Good resistant to chloride and fluoride solvents Good resistant to diluted mineral acids Good resistant to oils and petrol Good resistant to organic acids Good resistant to salts			

Complementary

Net Weight	0.11 lb(US) (0.05 kg)
Net Weight	0.11 lb(US) (0.05 kg)

Environment

protective treatment	TH TC
Ambient Air Temperature for Storage	-40.0000000000158.0000000000 °F (-4070 °C)
Ambient Air Temperature for Operation	-13.0000000000158.0000000000 °F (-2570 °C)
Overvoltage category	Class I IEC 60536 Class I NF C 20-030

Ordering and shipping details

Category	US10CS222475
Discount Schedule	0CS2
GTIN	3389110628005
Returnability	Yes
Country of origin	FR

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.06 in (2.7 cm)
Package 1 Width	5.08 in (12.9 cm)
Package 1 Length	6.1 in (15.6 cm)
Package 1 Weight	2.3 oz (64 g)
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	5.9 in (15 cm)
Package 2 Width	11.8 in (30 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	5.309 lb(US) (2.408 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	240
Package 3 Height	17.7 in (45 cm)
Package 3 Width	31.5 in (80 cm)
Package 3 Length	23.6 in (60 cm)
Package 3 Weight	61.209 lb(US) (27.764 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
Ø	Mercury Free	
	Rohs Exemption Information	Yes


Certifications & Standards

Reach Regulation	REACh Declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	No need of specific recycling operations		
California Proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		


Dimensions Drawings

Dimensions and Fixing

Below drawing shows a front plate with 4 cut-outs. Refer to the product characteristics to get the number of cut-outs.



Panel cut-out



b		b1		Н	
mm	in.	mm	in.	mm	in.
72	2.83	44	1.73	56	2.20