# **Product datasheet**

Specifications



## Red illuminated buzzer DC/AC24V

XB2BSB4LC

#### Main

Range Of Product	Easy Harmony XB2
Product Or Component Type	Annunciator
Bezel Material	Plastic
Mounting Diamete	22.5 mm
Cap/Operator Or Lens Colour	Red
Device Short Name	XB2
Light Source	LED

## Complementary

·				
Supply Circuit Type	AC/DC			
Supply Frequency	50/60 Hz			
Signalling Type	Intermittent tone			
Noise Level	90 dB 50 Hz55 Hz AC 90 dB 40 Hz45 Hz DC			
Shape Of Screw Head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver			
Height	30 mm			
Width	30 mm			
Depth	50 mm			
Net Weight	0.020 kg			
Current Consumption	<= 20 mA			
Shape Of Signaling Unit Head	Round			
[Us] Rated Supply Voltage	24 V +/- 10 %			
Operating Position	Any position			
Service Life In Hours	20000 h			
[Ui] Rated Insulation Voltage	400 V (pollution degree 3) conforming to EN/IEC 60947-1			
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to EN/IEC 60947-1			

### Environment

Protective Treatment	тс
Ambient Air Temperature For Storage	-4080 °C

Ambient Air Temperature For Operation	-2570 °C				
Overvoltage Category	Class II conforming to IEC 60536				
Standards	EN/IEC 60947-5-1 EN/IEC 60947-1 GB/T 14048.1 GB/T 14048.5				
Product Certifications	CCC CE				
Ip Degree Of Protection	IP40				
Ik Degree Of Protection	IK06				

## **Packing Units**

J	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.001 cm
Package 1 Width	2.98 cm
Package 1 Length	5.7 cm
Package 1 Weight	10 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	100
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.315 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	2000
Package 3 Height	90 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	34.8 kg

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Mercury Free
Rohs Exemption Information Yes


#### **Certifications & Standards**

Reach Regulation	REACh Declaration		
Eu Rohs Directive	Compliant EU RoHS Declaration		
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		
Circularity Profile	No need of specific recycling operations		

### **Product datasheet**

#### **Dimensions Drawings**

#### Dimensions



e: clamping thickness 1 to 6 mm / 0.04 to 0.24 in.


4

### **Product datasheet**

#### Mounting and Clearance

#### Mounting and Clearance

#### Panel cut-out



	Connection by Screw clamp terminals					
	a in mm	a in in.	b in mm	b in in.		
XB2BS•••	40	1.57	30	1.18		
XB2BV•••	40	1.57	30	1.18		

(1) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm  $_0^{+0.4}$  / 0.88 in.  $_0^{+0.016}$ )