



Selector switch, metal, black, Ø22, 2 positions, stay put, 1 NO Local distributor code:

23706187

XB4BD21

EAN Code: 3389110887075

Main

Range of product	Harmony XB4		
Product or component type	Selector switch		
Device short name	XB4		
Bezel material	Chromium plated metal		
Fixing collar material	Zamak		
Mounting diameter	22.5 mm		
Sale per indivisible quantity	1		
Head type	Standard		
Shape of signaling unit head	Round		
Type of operator	stay put		
Operator profile	Black standard handle		
Operator position information	2 positions 90°		
Contacts type and composition	n 1 NO		
Contact operation	Slow-break		
Connections - terminals	Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to IEC 60947-1 Screw clamp terminals, >= 1 x 0.22 mm² without cable end conforming to IEC 60947-1		

Complementary

Height	47 mm	
Width	30 mm	
Depth	68 mm	
Terminals description ISO n°1	(13-14)NO	
Net weight	0.095 kg	
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m	
Contacts usage	Standard contacts	
Positive opening	Without	
Torque value	0.14 N.m NO changing electrical state	
Mechanical durability	1000000 cycles	
Tightening torque	0.81.2 N.m conforming to IEC 60947-1	

Shape of screw head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver		
Contacts material	Silver alloy (Ag/Ni)		
Short-circuit protection	10 A cartridge fuse type gG conforming to IEC 60947-5-1		
[Ith] conventional free air thermal current	10 A conforming to IEC 60947-5-1		
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to IEC 60947-1		
[Uimp] rated impulse withstand voltage	Ise withstand 6 kV conforming to IEC 60947-1		
[le] rated operational current	3 A at 240 V, AC-15, A600 conforming to IEC 60947-5-1 6 A at 120 V, AC-15, A600 conforming to IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to IEC 60947-5-1		
Electrical durability	1000000 cycles, AC-15, 2 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN 60947-5-1 appendix C 1000000 cycles, AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN 60947-5-1 appendix C 1000000 cycles, AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN 60947-5-1 appendix C 1000000 cycles, DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN 60947-5-1 appendix C 1000000 cycles, DC-13, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN 60947-5-1 appendix C		
Electrical reliability	Λ < 10exp(-6) at 5 V and 1 mA in clean environment conforming to IEC 60947-5-4 Λ < 10exp(-8) at 17 V and 5 mA in clean environment conforming to IEC 60947-5-4		
Device presentation	Complete product		
Environment			
Protective treatment	тн		
Ambient air temperature for storage	-4070 °C		
Ambient air temperature for	-40 70 °C		

Protective treatment	тн			
Ambient air temperature for storage	e for -4070 °C			
Ambient air temperature for operation	re for -4070 °C			
Overvoltage category	Class I conforming to IEC 60536			
IP degree of protection	IP69 IP69K IP67 conforming to IEC 60529			
NEMA degree of protection	NEMA 13 NEMA 4X			
Standards	CSA C22.2 No 14 IEC 60947-5-1 JIS C8201-5-1 IEC 60947-1 IEC 60947-5-4 IEC 60947-5-5 UL 508 JIS C8201-1			
Product certifications	BV UL CSA DNV LROS (Lloyds register of shipping)			
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6			
30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27				

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.400 cm
Package 1 Width	5.300 cm
Package 1 Length	8.900 cm
Package 1 Weight	96.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	9.000 cm
Package 2 Width	3.400 cm
Package 2 Length	26.500 cm
Package 2 Weight	480.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	100
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	10.055 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes


Certifications & Standards

Reach Regulation	REACh Declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		
Circularity Profile	End of Life Information		

26 Oct 2024

Dimensions Drawings

Dimensions



e: clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.


XB4BD21


Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board

Connection by Faston Connectors







- (1) Diameter on finished panel or support
- (2) 40 mm min. / 1.57 in. min.
- (3) 30 mm min. / 1.18 in. min.
- (4) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm $_0^{+0.4}$ / 0.88 in. $_0^{+0.016}$)
- (5) 45 mm min. / 1.78 in. min.
- (6) 32 mm min. / 1.26 in. min.

Technical Illustration

Dimensions





	a (mm)	a (in.)	b (mm)	b (m.)
ZBE ZBV	40	1.57	30	1.18
ZBE3 ZBV3		1.77	32	1.26
ZBE4 ZBV4		1,57	30	1.18
ZBE5 ZBV5	50	1.97	30	1.18
ZBE•••••9 ZBV••••9	40	1.57	30	1.18
ZBRT• ZBRV1	40	1.57	30	1,18

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB4



Image of product / Alternate images

Alternative









11





