Product data sheet

Specification





pilot light, Harmony XB5, grey plastic, red, 22mm, universal LED, plain lens, 110...120V AC

XB5AVG4

Product availability: Stock - Normally stocked in distribution facility

Important message: A change in appearance may be noted on the product but does not affect its use in terms of function and safety. This makes it compatible with our Universal LED blocks

Price*: 72.00 USD

Main

| Range of Product | Harmony XB5 |
|---------------------------------|----------------------|
| Product or Component Type | Pilot light |
| Device short name | XB5 |
| Bezel material | Dark grey plastic |
| Fixing collar material | Plastic |
| Head type | Standard |
| Mounting diameter | 0.9 in (22.5 mm) |
| Sale per indivisible quantity | 1 |
| Shape of signaling unit head | Round |
| Cap/operator or lens colour | Red |
| Operator additional information | With plain lens |
| Light source | Universal LED |
| Bulb base | Integral LED |
| Light source colour | Red |
| [Us] rated supply voltage | 110120 V AC 50/60 Hz |
| device presentation | Complete product |

Complementary

| • | | | | | | |
|--|--|--|--|--|--|--|
| Height | 1.7 in (42 mm) | | | | | |
| Width | 1.2 in (30 mm) | | | | | |
| Depth | 2.1 in (54 mm) | | | | | |
| Terminals description ISO n°1 | (X1-X2)PL | | | | | |
| Net Weight | 0.084 lb(US) (0.038 kg) | | | | | |
| Resistance to high pressure washer | 1015.3 psi (7000000 Pa) 131.00000000000 °F (55 °C) 0.1 m | | | | | |
| Connections - terminals | Screw clamp terminals, <= 2 x 1.5 mm ² with cable end IEC 60947-1 Screw clamp terminals, 1 x 0.222 x 2.5 mm ² without cable end IEC 60947-1 | | | | | |
| [Ui] rated insulation voltage | 250 V 3)IEC 60947-1 | | | | | |
| [Uimp] rated impulse withstand voltage | 4 kV IEC 60947-1 | | | | | |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Signalling type | Steady |
|-----------------------|-------------------------------------|
| GCR BRIDGE | XB5AVCUST04 |
| Compatibility code | XB5 |
| Supply voltage limits | 100132 V AC |
| Current Consumption | 14 mA |
| Service life | 100000 h at rated voltage and 25 °C |
| Surge withstand | 1 kV IEC 61000-4-5 |

Environment

| protective treatment | тн | | | | |
|--|--|--|--|--|--|
| Ambient Air Temperature for Storage | -40.0000000000158.0000000000 °F (-4070 °C) | | | | |
| Ambient Air Temperature for Operation | -40.0000000000158.00000000000 °F (-4070 °C) | | | | |
| Overvoltage category | Class II IEC 60536 | | | | |
| IP degree of protection | IP66 IEC 60529 IP67 IEC 60529 IP69 IEC 60529 IP69K ISO 20653 | | | | |
| NEMA degree of protection | NEMA 13 NEMA 4X | | | | |
| IK degree of protection | IK05 conforming to IEC 50102 | | | | |
| Standards | IEC 60947-1 IEC 60947-5-1 UL 508 IEC 60947-5-4 JIS C8201-5-1 CSA C22.2 No 14 JIS C8201-1 | | | | |
| Product Certifications | UL Listed CSA | | | | |
| Vibration resistance | 5 gn 12500 Hz)IEC 60068-2-6 | | | | |
| Shock resistance | 50 gn 18 ms) half sine wave acceleration IEC 60068-2-27 30 gn 11 ms) half sine wave acceleration IEC 60068-2-27 | | | | |
| Resistance to fast transients | 2 kV IEC 61000-4-4 | | | | |
| Resistance to electromagnetic fields | 9.1 V/m (10 V/m) IEC 61000-4-3 | | | | |
| Electromagnetic compatibility | Electrostatic discharge - test level: 6 kV (on contact (on metal parts)) conforming to IEC 61000-4-2 Electrostatic discharge - test level: 8 kV (in free air (in insulating parts)) conforming to IEC 61000-4-2 Electromagnetic emission class B conforming to IEC 55011 | | | | |
| Resistance to electrostatic discharge | 6 kV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2 | | | | |
| Electromagnetic emission | Class B IEC 55011 | | | | |

Ordering and shipping details

| Category | US10CS222467 |
|-------------------|---------------|
| Discount Schedule | 0CS2 |
| GTIN | 3389110903829 |
| Returnability | Yes |
| Country of origin | FR |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.3 in (3.4 cm) |
| Package 1 Width | 2.1 in (5.4 cm) |
| Package 1 Length | 3.5 in (8.8 cm) |
| Package 1 Weight | 1.2 oz (35.0 g) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 50 |
| Package 2 Height | 5.9 in (15 cm) |
| Package 2 Width | 11.8 in (30 cm) |
| Package 2 Length | 15.7 in (40 cm) |
| Package 2 Weight | 4.588 lb(US) (2.081 kg) |

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards


| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) | | |
|---------------------------|---|--|--|
| China Rohs Regulation | China RoHS declaration | | |
| Environmental Disclosure | Product Environmental Profile | | |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. | | |
| Circularity Profile | End of Life Information | | |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov | | |

Product data sheet

XB5AVG4

Dimensions Drawings

Dimensions



 $\boldsymbol{e}\text{:}$ clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.


b: 30 mm / 1.18 in. **c:** 41.5 mm / 1.63 in.

XB5AVG4

Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for


Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3) Ø22.5 mm recommended (Ø22.3 $_0^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 in. $_0^{+0.016}$)

| | | | | • |
|---|---------|----------|---------|----------|
| Connections | a in mm | a in in. | b in mm | b in in. |
| By screw clamp terminals or plug-in connector | 40 | 1.57 | 30 | 1.18 |
| By Faston connectors | 45 | 1.77 | 32 | 1.26 |
| On printed circuit board | 30 | 1.18 | 30 | 1.18 |

Detail of Lug Recess



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended. (3) \emptyset 22.5 mm recommended (\emptyset 22.3 $_0^{+0.4}$) / \emptyset 0.89 in. recommended (\emptyset 0.88 in. $_0^{+0.016}$)