# **Product datasheet**

Specification





Illuminated emergency switching off push button, Harmony XB5N XB7N, plastic, red, 40mm, turn to release, 24V AC DC, 1 NC

XB5AW74B2N

#### Main

Harmony XB5N/XB7N
Illuminated emergency switching off push-button
XB5N
Dark grey plastic
Plastic
22.5 mm
20
LED
24 V
Round
turn to release
Red flush, unmarked
Slow-break
Screw clamp terminal, <= 2 x 1.5 mm² with cable end conforming to IEC 60947-1 Screw clamp terminal, >= 1 x 0.22 mm² without cable end conforming to IEC 60947-1
Complete product
1 NC

## Complementary

Supply voltage limits	19.230 V DC 21.626.4 V AC
Height	42 mm
Width	40 mm
Depth	82.5 mm
Terminals description ISO n°1	(21-22)NC
Net weight	0.057 kg
Device mounting	Fixing hole - diameter: 22.5 mm 22.3 +0.4/0 conforming to IEC 60947-5-1
Fixing mode	Fixing nut recommended torque: 2.2 N.m (+/- 0.2 N.m)
marking	Unmarked
Contacts usage	Standard contacts
Positive opening	With conforming to IEC 60947-5-1 appendix K

Operating travel	1.5 mm (NC changing electrical state) 2.6 mm (NO changing electrical state)
	4.3 mm (total travel)
Operating force	3.5 N NC changing electrical state 3.8 N NO changing electrical state
Mechanical durability	300000 cycles
Tightening torque	0.81.2 N.m conforming to IEC 60947-1
Shape of screw head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver
	Slotted compatible with flat $\emptyset$ 4 mm screwdriver Slotted compatible with flat $\emptyset$ 5.5 mm screwdriver
Contacts material	Silver alloy (Ag/Ni)
Short-circuit protection	10 A cartridge fuse type gG conforming to IEC 60947-5-1
[Ith] conventional free air thermal current	10 A conforming to IEC 60947-5-1
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to IEC 60947-1
Resistance to electrostatic discharge	6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-1
[le] rated operational current	3 A at 240 V, AC-15, A600 conforming to IEC 60947-5-1
•	6 A at 120 V, AC-15, A600 conforming to IEC 60947-5-1
	0.1 A at 600 V, DC-13, Q600 conforming to IEC 60947-5-1
	0.27 A at 250 V, DC-13, Q600 conforming to IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to IEC 60947-5-1
	1.2 A at 600 V, AC-15, A600 conforming to IEC 60947-5-1
Electrical durability	1000000 cycles, AC-15, 2 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5
	conforming to IEC 60947-5-1 appendix C
	1000000 cycles, AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
	1000000 cycles, AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5
	conforming to IEC 60947-5-1 appendix C
	1000000 cycles, DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
	1000000 cycles, DC-13, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Electrical reliability	$\Lambda$ < 10exp(-6) at 5 V, 1 mA in clean environment conforming to IEC 60947-5-4 $\Lambda$ < 10exp(-8) at 17 V, 5 mA in clean environment conforming to IEC 60947-5-4
Compatibility code	XB5
Product compatibility	ZB5N
Environment	
protective treatment	TH
Ambient air temperature for	-4070 °C
storage  Ambient air temperature for	
operation	-2570 °C
Overvoltage category	Class II conforming to IEC 60536
Standards	IEC 60947-5-4
	IEC 60947-1 IEC 60947-5-1
	IS 13947-5-1
Product certifications	CE
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC
	60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC
	60068-2-27

IP degree of protection	IP65	
IK degree of protection	IK03	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.2 cm
Package 1 Width	3.3 cm
Package 1 Length	5.2 cm
Package 1 Weight	122.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	240
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

03-Sept-2024