# Product data sheet





# Complete illuminated push button, Harmony XB6, white square flush, 16mm, spring return 1NO 12...24V

XB6CW1B1B

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 44.40 USD

#### Main

Range Of Product	Harmony XB6	
Product Or Component Type	Complete illuminated push-button	
Device Short Name	XB6	
Bezel Material	Plastic	
Mounting Diamete	0.63 in (16 mm)	
Sale Per Indivisible Quantity	1	
Shape Of Signaling Unit Head	Square	
Type Of Operator	spring return	
Operator Profile	White flush, unmarked	
Contacts Type And Composition	1 NO	
Contact Operation	Slow-break	
Connections - Terminals	Faston connectors 2.8 x 0.5 mm	
Light Source	LED	
Bulb Base	Integral LED	
[Us] Rated Supply Voltage	1224 V AC/DC	

#### Complementary

Cad Overall Width	0.71 in (18 mm)	
Cad Overall Height	0.71 in (18 mm)	
Cad Overall Depth	2.24 in (57 mm)	
Terminals Description Iso N°1	(13-14)NO	
Net Weight	0.05 lb(US) (0.022 kg)	
Operating Position	Any position	
Positive Opening	With IEC 60947-5-1 appendix K	
Operating Travel	0.04 in (1 mm) NO changing electrical state) 0.14 in (3.5 mm) total travel)	
Operating Force	3.5 N NO changing electrical state	
Contacts Material	Silver alloy (Ag/Ni)	
Short-Circuit Protection	6 A cartridge fuse gG	
[Ui] Rated Insulation Voltage	250 V 3)IEC 60947-1	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

[Uimp] Rated Impulse Withstand Voltage	4 kV IEC 60947-1	
[le] Rated Operational Current	3 A 120 V, AC-15, B300 IEC 60947-5-1 1.5 A 240 V, AC-15, B300 IEC 60947-5-1 0.1 A 250 V, DC-13, R300 IEC 60947-5-1 0.22 A 125 V, DC-13, R300 IEC 60947-5-1	
Electrical Durability	1000000 cycles, AC-15 230 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C 1000000 cycles, DC-13 230 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C	
Electrical Reliability	Λ = 10exp(-8) 5 V 1 mA with confidence level of 90 % IEC 60947-5-4	
Signalling Type	Steady	
Supply Voltage Limits	630 V AC/DC	
Current Consumption	15 mA	
Surge Withstand	1 kV direct contact IEC 61000-4-5 2 kV in free air IEC 61000-4-5	

## **Environment**

Protective Treatment	TC
Ambient Air Temperature For Storage	-40158 °F (-4070 °C)
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)
<b>Electrical Shock Protection Class</b>	Class II IEC 61140
Ip Degree Of Protection	IP65 IEC 60529
Nema Degree Of Protection	NEMA 13 UL 50 NEMA 4 UL 50 NEMA 4X UL 50 NEMA 13 CSA C22.2 No 94 NEMA 4 CSA C22.2 No 94 NEMA 4X CSA C22.2 No 94
Standards	IEC 60947-1 IEC 60947-5-1 CSA C22.2 No 14 JIS C 4520 JIS C 852 IEC 60947-5-5
Product Certifications	CSA CCC UL GOST
Vibration Resistance	+/- 3 mm 2500 Hz)IEC 60068-2-6 5 gn 2500 Hz)IEC 60068-2-6
Shock Resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27
Resistance To Fast Transients	2 kV IEC 61000-4-4
Resistance To Electromagnetic Fields	9.14 V/m (10 V/m) IEC 61000-4-3
Resistance To Electrostatic Discharge	6 kV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2
Electromagnetic Emission	Class B IEC 55011

# Ordering and shipping details

Category	US10CS222459
Discount Schedule	0CS2
Gtin	3389110763713
Returnability	No

Country Of Origin MX

# **Packing Units**

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	4.33 in (11.0 cm)
Package 1 Length	6.30 in (16.0 cm)
Package 1 Weight	0.53 oz (15.0 g)
Unit Type Of Package 2	S01
Number Of Units In Package 2	60
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	5.91 in (15.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	2.37 lb(US) (1.077 kg)

# **Contractual warranty**

Warranty 18 months

# Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


## **Product data sheet**

### XB6CW1B1B

#### **Dimensions Drawings**

#### **Square Head Pushbutton**

#### **Dimensions**



e panel thickness 1 to 6 mm/0.03 to 0.23 in.

## **Product data sheet**

### XB6CW1B1B

Mounting and Clearance

#### Panel Cut-out

#### For Square or Circular Head

