Product data sheet

Specification





Monolithic push button, Harmony XB7, plastic, green, 22mm, spring return, unmarked, 1NO

XB7NA31

Product availability: Stock - Normally stocked in distribution facility

Price*: 19.25 USD

Main

Range of Product	Harmony XB7	
Product or Component Type	Push-button	
Device short name	XB7	
Mounting diameter	0.9 in (22 mm)	
Sale per indivisible quantity	10	
IP degree of protection	IP20 IEC 60529 rear face) IP65 IEC 60529 front face)	
Shape of signaling unit head	Round	
Type of operator	spring return	
Operator profile	Green flush, unmarked	
Contacts type and composition	n 1 NO	
Connections - terminals	Screw clamp terminals, <= 2 x 1.5 mm² with cable end IEC 60947-1 Screw clamp terminals, 1 x 0.342 x 2.5 mm² without cable end IEC 60947-1	
device presentation	Monolithic product	

Complementary

CAD overall width	1.1 in (29 mm)	
CAD overall height	1.1 in (29 mm)	
CAD overall depth	2.03 in (51.5 mm)	
Terminals description ISO n°1	(13-14)NO	
Net Weight	0.046 lb(US) (0.021 kg)	
Device mounting	Fixing hole 0.9 in (22.5 mm) 22.3 +0.4/0 IEC 60947-1	
Fixing center	>= 30 x 40 mm support panel) metal 0.040.2 in (16 mm) >= 30 x 40 mm support panel) plastic 0.080.2 in (26 mm)	
Fixing mode	Fixing nut beneath head 17.721.2 lbf.in (22.4 N.m)	
Contact operation	Slow-break	
Positive opening	With (only NO)	
Mechanical durability	1000000 cycles	
Tightening torque	7.0810.6 lbf.in (0.81.2 N.m) IEC 60947-1	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Shape of screw head	Cross JIS No 1 Cross Philips no 1 Cross pozidriv No 1 Slotted flat Ø 4 mm Slotted flat Ø 5.5 mm
Short-circuit protection	4 A cartridge fuse gG IEC 60947-5-1
[Ui] rated insulation voltage	250 V 3)IEC 60947-1
[Uimp] rated impulse withstand voltage	4 kV IEC 60947-1
[le] rated operational current	0.1 A 250 V, DC-13, R300 IEC 60947-5-1 0.22 A 125 V, DC-13, R300 IEC 60947-5-1 0.3 A 240 V, AC-14, D300 IEC 60947-5-1 0.6 A 120 V, AC-14, D300 IEC 60947-5-1
Electrical durability	1000000 cycles, DC-13, 0.3 A 24 V 216000 cyc/mn 0.5 IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 0.03 A 230 V 216000 cyc/mn 0.5 IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 0.09 A 240 V 108000 cyc/mn 0.5 IEC 60947-5-1 appendix C
Electrical reliability	Λ <= 10exp(-6) 17 V, 5 mA IEC 60947-5-4

Environment

protective treatment	тн	
Ambient Air Temperature for Storage	-40.0000000000158.0000000000 °F (-4070 °C)	
Ambient Air Temperature for Operation	-13.0000000000158.0000000000 °F (-2570 °C)	
Overvoltage category	Class II IEC 61140	
NEMA degree of protection	NEMA 12 UL 50 E NEMA 3 UL 50 E	
Standards	UL 508 CSA C22.2 No 14 JIS C8201-5-1 IEC 60947-5-1 IEC 60947-1 JIS C8201-1	
Product Certifications	GOST CCC	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	50 gn 11 ms) half sine wave acceleration IEC 60068-2-27 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27	

Ordering and shipping details

Category	US10CS222464	
Discount Schedule	0CS2	
GTIN	3606480470011	
Returnability	Yes	
Country of origin	ID	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 in (7.0 cm)
Package 1 Width	3.7 in (9.5 cm)
Package 1 Length	5.9 in (15.0 cm)

Package 1 Weight	0.7 oz (20.0 g)
Unit Type of Package 2	BAG
Number of Units in Package 2	10
Package 2 Height	3.9 in (10.0 cm)
Package 2 Width	2.8 in (7.0 cm)
Package 2 Length	5.9 in (15.0 cm)
Package 2 Weight	7.05 oz (200.0 g)
Unit Type of Package 3	S01
Number of Units in Package 3	100
Package 3 Height	5.9 in (15.0 cm)
Package 3 Width	5.9 in (15.0 cm)
Package 3 Length	15.7 in (40.0 cm)
Package 3 Weight	4.905 lb(US) (2.225 ka)

Contractual warranty

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Toxic Heavy Metal Free	
⊘	Mercury Free	
②	Rohs Exemption Information	Yes

Certifications & Standards

Pro-active compliance (Product out of EU RoHS legal scope)
EU RoHS Declaration
China RoHS declaration
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
End of Life Information
WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


Sep 4, 2024

XB7NA31

Dimensions Drawings

Pushbutton, Flush Type

Dimensions




e Support panel thickness: 1 to 6 mm/0.4 to 0.24 in. (metal), 2 to 6 mm/0.8 to 0.24 in. (plastic).

XB7NA31

Mounting and Clearance


Mounting

Diameter of Finished Fixing Holes



- (1) Minimum value.
- (2) 40 mm/1.58 in. for Emergency switching off pushbutton only.
- (3) Standard value: Ø 22.3 (0; + 0.4) mm/Ø 0.88 (0; + 0.02) in.

"U" Type Tag Connection



- (1) 6.5 mm/0.26 in. recommended, 7 mm/0.28 in. max.
- (2) M3 screw clamp terminal.

Product data sheet

XB7NA31

Connections and Schema

Wiring Diagram

