

# XCSLF2727313

Safety switch, Telemecanique Safety switches XCS, metal XCSLF, 4 NC, slow break, 3 entries tapped 1/2" NPT, 24 V



## Main

|  |  |
|--|--|
| Range of product                       | Telemecanique Safety switches XCS  |
| Product or component type              | Safety switch  |
| Component name                         | XCSLF  |
| Design                                 | Slim   |
| Material                               | Metal  |
| Head type                              | Key operated turret head   |
| Contacts type and composition          | 2 NC   |
| Contact operation                      | Slow-break, simultaneous   |
| Solenoid contacts type and composition | 2 NC (slow-break, simultaneous)  |
| Cable entry                            | 3 entries tapped for 1/2" NPT  |
| Electromagnet interlocking             | Locking on de-energisation and unlocking on energisation of solenoid   |
| [Us] solenoid rated supply voltage     | 24 V AC/DC   |
| Electrical connection                  | Spring terminal, clamping capacity: 1 x 1.5 mm <sup>2</sup> flexible or solid cable<br>Spring terminal, clamping capacity: 2 x 0.5 mm <sup>2</sup> flexible cables with 13 mm bared ends |
| Number of poles                        | 2  |
| Locking options description            | With interlocking, locking by solenoid   |
| Local signalling                       | 1 LED (orange) for actuator withdrawn<br>1 LED (green) for actuator inserted and locked  |
| Signalling circuit voltage             | 24 V   |

## Complementary

|  |  |
|--|--|
| Positive opening                             | With NC contact  |
| Supply voltage type                          | AC/DC  |
| Supply frequency                             | 50/60 Hz   |
| Load factor                                  | 1  |
| Signalling circuit type                      | AC/DC  |
| Mechanical durability                        | 1000000 cycles   |
| Minimum actuation speed                      | 0.01 m/s   |
| Maximum actuation speed                      | 0.5 m/s  |
| [Ie] rated operational current               | 0.55 A at 24 V, DC-13, R300 conforming to EN/IEC 60947-5-1<br>0.75 A at 240 V, AC-15, C300 conforming to EN/IEC 60947-5-1    |
| [Ithe] conventional enclosed thermal current | 4 A  |
| Maximum load current                         | <= 15 A  |
| [Ui] rated insulation voltage                | 300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14<br>250 V (pollution degree 3) conforming to EN/IEC 60947-1 |
| [Uimp] rated impulse withstand voltage       | 4 kV conforming to EN/IEC 60947-5-1  |
| Minimum switching current                    | 10 mA at 20 °C   |
| Minimum switching voltage                    | 17 V   |
| Short-circuit protection                     | 4 A cartridge fuse type gG (gl)<br>6 A type fast blow  |
| Maximum actuator forcible withdrawal rtc     | 3000 N   |

|                                       |  |
|---------------------------------------|--|
| Minimum actuator force for extraction | 20 N   |
| Resistance to mechanical impact       | 9.6 J against the partition<br>6.4 J without partition   |
| Maximum operating rate                | 10 cyc/mn for maximum durability   |
| Safety level                          | Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach SIL 3 conforming to EN/IEC 61508 |
| Safety reliability data               | B10d = 5500000 value given for a life time of 20 years limited by mechanical or contact wear   |
| Body material                         | Zamak  |
| Head material                         | Zamak  |
| Depth                                 | 51 mm  |
| Height                                | 205 mm   |
| Width                                 | 44 mm  |
| Net weight                            | 1.1 kg   |

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | UL 508<br>EN 1088/ISO 14119<br>EN/ISO 13849-1<br>EN/IEC 60947-5-1<br>EN/IEC 62061<br>EN/IEC 60204-1<br>CSA C22.2 No 14 |
| Product certifications                | UL[RETURN]CSA[RETURN]TÜV   |
| Protective treatment                  | TC   |
| Ambient air temperature for operation | -25...60 °C  |
| Ambient air temperature for storage   | -40...70 °C  |
| Vibration resistance                  | 5 gn (f= 10...500 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                      | 10 gn for 11 ms conforming to IEC 60068-2-27   |
| Electrical shock protection class     | Class I conforming to EN/IEC 61140   |
| IP degree of protection               | IP66 conforming to EN/IEC 60529 and EN/IEC 60947-5-1<br>IP67   |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 5.6 cm    |
| Package 1 Width              | 7.5 cm    |
| Package 1 Length             | 22.9 cm   |
| Package 1 Weight             | 1.27 kg   |
| Unit Type of Package 2       | S02       |
| Number of Units in Package 2 | 8         |
| Package 2 Height             | 15 cm     |
| Package 2 Width              | 30 cm     |
| Package 2 Length             | 40 cm     |
| Package 2 Weight             | 10.615 kg |

## Offer Sustainability

|  |   |
|--|---|
| Sustainable offer status                   | Green Premium product   |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|