XE3SP2141

Limit switch contact block, Limit switches XC Standard, 2NC+1 NO, snap action



Main

| Range of product | Telemecanique Limit switches XC Standard |
|-------------------------------|--|
| Series name | Standard format |
| Product or component type | Limit switch contact block |
| Device short name | XE3S |
| Associated body | ZCD39 ZCP39 ZCKLD39 ZCKMD39 ZCKJD39 ZXKSD39 |
| Number of poles | 3 |
| Contacts type and composition | 1 NO + 2 NC |
| Contact operation | Snap action |

Complementary

| Product compatibility | XCKD |
|--|---|
| Troduct compatisinty | XCKP |
| | XCKM |
| | XCKS |
| | XCKJ |
| | XCKL |
| Electrical connection | Screw-clamp terminals, clamping capacity: 1 x 0.342 x 0.75 mm ² |
| Contacts insulation form | Zb |
| Contacts material | Silver plated contacts |
| Positive opening | With |
| Minimum actuation speed | 0.01 mm/s |
| Contact code designation | B300, AC-15 (Ue = 240 V), le = 1.5 A, Ithe = 6 A conforming to IEC 60947-5-1 |
| | appendix A |
| | R300, DC-13 (Ue = 250 V), le = 0.1 A conforming to IEC 60947-5-1 appendix A |
| Maximum resistance across terminals | 25 mOhm conforming to IEC 60255-7 category 3 |
| [Ui] rated insulation voltage | 300 V conforming to UL 508 |
| | 300 V conforming to CSA C22.2 No 14 |
| | 400 V (pollution degree 3) conforming to IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 4 KV conforming to IEC 60664 |
| | 4 kV conforming to IEC 60947-1 |
| Short-circuit protection | 6 A cartridge fuse, type gG |
| Electrical durability | 5000000 Cycles, DC-13 120 V, 1 W, operating rate <60 cyc/mn, load factor: 0.5 |
| | conforming to IEC 60947-5-1 appendix C |
| | 5000000 Cycles, DC-13 24 V, 3 W, operating rate <60 cyc/mn, load factor: 0.5 |
| | conforming to IEC 60947-5-1 appendix C |
| | 5000000 cycles, DC-13 48 V, 2 W, operating rate <60 cyc/mn, load factor: 0.5 |
| | conforming to IEC 60947-5-1 appendix C |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|----------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 2.500 cm | |
| Package 1 Width | 4.000 cm | |
| Package 1 Length | 5.000 cm | |
| Package 1 Weight | 23.000 g | |
| Unit Type of Package 2 | S01 | |

| Number of Units in Package 2 | 100 |
|------------------------------|-----------|
| Package 2 Height | 15.000 cm |
| Package 2 Width | 15.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 2.513 kg |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|--|---|
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| Warranty 18 months | |
|--------------------|--|
|--------------------|--|

