



Harmony, XAC Pendant Station, contact block, spring return, front mounting, 1 early close NO, 1 NO and 1 NC

XENG1191

Product availability: Stock - Normally stocked in distribution facility

Price*: 49.00 USD

Main

Range of Product	Harmony XAC	
Product or Component Type	Contact block	
Component name	XENG	
Electrical circuit type	Control circuit	
Contact block application	2-speed	
Contact block type	Single	
Type of operator	Spring return	
Product Compatibility	XACA XACA9head	
Contacts type and composition	1 NC + 2 NO	
Mounting of block	Front mounting	
Contact operation	Slow-break Staggered	

Complementary

Connections - terminals	Screw clamp terminals, 1 x 0.51 x 2.5 mm² without cable end Screw clamp terminals, 1 x 0.52 x 1.5 mm² with cable end	
Mechanical durability	1000000 cycles	
Contact code designation	A600 AC-15, Ue = 240 V, Ie = 3 A IEC 60947-5-1 appendix A A600 AC-15, Ue = 600 V, Ie = 1.2 A IEC 60947-5-1 appendix A Q600 DC-13, Ue = 250 V, Ie = 0.27 A IEC 60947-5-1 appendix A Q600 DC-13, Ue = 600 V, Ie = 0.1 A IEC 60947-5-1 appendix A	
[Ithe] conventional enclosed thermal current	10 A	
[Ui] rated insulation voltage	600 V 3)IEC 60947-1	
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-1	
Maximum resistance across terminals	25 MOhm	
Operating force	18 N	
Short-circuit protection	10 A fuse protection cartridge gG	
Rated operational power in W	40 W DC-13 1000000 cycles 60 cyc/mn 120 V 0.5 inductive IEC 60947-5-1 appendix C 48 W DC-13 1000000 cycles 60 cyc/mn 48 V 0.5 inductive IEC 60947-5-1 appendix C 65 W DC-13 1000000 cycles 60 cyc/mn 24 V 0.5 inductive IEC 60947-5-1 appendix C	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Terminals description ISO n°1	(21-22)NC (33-34)NO_CL (13-14)NO
Net Weight	0.09 lb(US) (0.04 kg)

Environment

Standards	UL 508 EN/IEC 60947-5-1 CSA C22.2 No 14
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Vibration resistance	15 gn 10500 Hz)IEC 60068-2-6
Shock resistance	100 gn IEC 60068-2-27
Overvoltage category	Class II IEC 61140

Ordering and shipping details

Category	US10CS222466	
Discount Schedule	0CS2	
GTIN	3389110645705	
Returnability	Yes	
Country of origin	CZ	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.2 in (3.0 cm)	
Package 1 Width	1.6 in (4.0 cm)	
Package 1 Length	2.2 in (5.5 cm)	
Package 1 Weight	1.5 oz (42.0 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	100	
Package 2 Height	5.9 in (15.0 cm)	
Package 2 Width	11.8 in (30.0 cm)	
Package 2 Length	15.7 in (40.0 cm)	
Package 2 Weight	10.03 lb(US) (4.55 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	1600	
Package 3 Height	30.3 in (77.0 cm)	
Package 3 Width	31.5 in (80.0 cm)	
Package 3 Length	23.6 in (60.0 cm)	
Package 3 Weight	179.2 lb(US) (81.3 kg)	

Contractual warranty

Warranty

18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
Ø	Mercury Free	
9	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Image of product / Alternate images

Alternative







