

XGSZ09L10

Radio frequency identification XG, pre wired
M12 female connector, cable 10 m, IP67



Main

Range of product	Telemecanique Radio frequency identification XG
Accessory / separate part categor	Connection accessories
Accessory / separate part type	Connecting cable
Accessory / separate part designation	Pre-wired M12 female connector
Accessory / separate part destination	For 24 V DC supply of connection box
Cable length	10 m

Complementary

Product compatibility	XGSZ33ETH TCSAMT31FP
Electrical connection	1 female connector M12 4 pins A coding
Colour	Black
Net weight	0.52 kg

Environment

IP degree of protection	IP67
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	18.000 cm
Package 1 Length	18.000 cm
Package 1 Weight	343.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.812 kg

Offer Sustainability


Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------

Wiring Diagram

Modbus Connections



Pin no.		Signal
1	Red	+ 24 VDC
2	NC	-
3	Black	0 VDC
4	NC	-