

# XMLR010G2P25

Electronic pressure sensors, Pressure sensors  
XM, XMLR 10 bar, G 1/4, 24 VDC, 4...20 mA,  
2xPNP, M12

## Main

Range of Product	Telemecanique Pressure sensors XM
Product or Component Type	Electronic pressure sensors
Pressure sensor type	Pressure transmitter
Pressure switch type of operation	Pressure transmitter with 2 switching outputs
Device short name	XMLR
Pressure Rating	145 Psi (999.7 kPa) 145.04 psi (10 bar)
Maximum permissible accidental pressure	4 MPa 580 Psi (3999.0 kPa) 580.2 psi (40 bar)
Destruction pressure	580 Psi (3999.0 kPa) 580.2 Psi (40 bar) 4 MPa
Controlled fluid	Fresh water 32.0000000000...176.0000000000 °F (0...80 °C)) Air -4.0000000000...176.0000000000 °F (-20...80 °C)) Hydraulic oil -4.0000000000...176.0000000000 °F (-20...80 °C)) Refrigeration fluid -4.0000000000...176.0000000000 °F (-20...80 °C))
Fluid connection type	G 1/4 (female) DIN 3852-Y
[Us] rated supply voltage	24 V DC SELV 17...33 V)

## Complementary

Current Consumption	<= 50 mA
Electrical connection	Male connector M12, 5 pins
Analogue output function	4...20 mA
Type of output signal	Analogue + discrete
Analogue output function	4...20 mA
Discrete output type	Solid state PNP, 2 NO/NC programmable
Maximum switching current	250 mA
Contacts type and composition	2 NO/NC programmable
Scale type	Fixed differential
Maximum voltage drop	2 V
Adjustable range of switching point on rising pressure	11.6...145 Psi (80.0...999.7 kPa) 11.6...145.04 Psi (0.8...10 bar) 0.08...1 MPa
Adjustable range of switching point on falling pressure	7.3...140.7 Psi (0.5...9.7 bar) 0.05...0.97 MPa 7.25...141 psi (49.99...972.2 kPa)
Minimum differential travel	4.35 Psi (29.99 kPa) 4.4 Psi (0.3 bar) 4.4 psi (30 kPa)
Materials in contact with fluid	Ceramic Fluorocarbon FKM (Viton) 316L stainless steel
Front material	Polyester
Housing material	316L stainless steel Polyacrylamide

Operating position	Any position, but disposals can falsified the measurement in case of upside down mounting
Protection Type	Overload protection Overvoltage protection Reverse polarity Short-circuit protection
Response time on output	<= 10 ms analog output <= 5 ms discrete output
Switching output time delay	0...50 s in steps of 1 second
Display Type	4 digits 7 segments
Local signalling	for light ON when switch is actuated 2 LEDs (yellow)
Display response time type	Fast 50 ms Normal 200 ms Slow 600 ms
Maximum delay first up	300 ms
Overall accuracy	<= 1 % of the measuring range
Linearity error on analogue output	<= 0.5 % of the measuring range
Hysteresis on analogue output	<= 0.2 % of the measuring range
Measurement accuracy on switching output	<= 0.6 % of the measuring range
Repeat accuracy	<= 0.2 % of the measuring range
Drift of the sensitivity	+/- 0.03 % of measuring range/°C
Drift of the zero point	+/- 0.1 % of measuring range/°C
Display accuracy	<= 1 % of the measuring range
Mechanical durability	10000000 cycles
Depth	1.7 in (42 mm)
Height	3.7 in (93 mm)
Width	1.6 in (41 mm)
Net Weight	0.42 lb(US) (0.19 kg)
[Uimp] rated impulse withstand voltage	0.5 kV DC
Electromagnetic compatibility	Susceptibility to electromagnetic fields 10 V/m 80...2000 MHz IEC 61000-4-3 Immunity to conducted RF disturbances 10 V 0.15...80 MHz IEC 61000-4-6 Surge immunity test 1 kV IEC 61000-4-5 Electrical fast transient/burst immunity test 2 kV IEC 61000-4-4 Electrostatic discharge immunity test 8 kV air, 4 kV contact IEC 61000-4-2

## Environment

Marking	CE
Product Certifications	cULus
Standards	UL 61010-1 IEC 61326-2-3
Ambient Air Temperature for Operation	-4.0000000000...176.0000000000 °F (-20...80 °C)
Ambient Air Temperature for Storage	-40.0000000000...176.0000000000 °F (-40...80 °C)
IP degree of protection	IP65 conforming to IEC 60529 IP67 conforming to IEC 60529
Vibration resistance	20 gn 10...2000 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27

## Ordering and shipping details

Category	US10DS221551
Discount Schedule	0DS2
GTIN	3389119610575
Returnability	No
Country of origin	CH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.559 in (6.500 cm)
Package 1 Width	2.953 in (7.500 cm)
Package 1 Length	5.0000000000 in (12.700 cm)
Package 1 Weight	6.702 oz (190.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	5.9 in (15 cm)
Package 2 Width	11.8 in (30 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	9.107 lb(US) (4.131 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>