# **Product datasheet**

Specification





# single foot switch - IP43 - without cover - plastic - black - 2 NC + 2 NO

XPEA111

## Main

Range Of Product	Harmony XPE	
Product Or Component Type	Foot switch	
Material	Plastic	
Foot Switch Type	Single foot switch	
Device Short Name	XPEA	
Trigger Mechanism	Without trigger mechanism	
Contact Operation	1 step	
Contacts Type And Composition	2 NC + NO	
Colour	Black	

## Complementary

Positive Opening	With conforming to IEC 60947-5-1 appendix K
Connections - Terminals	Screw clamp terminal, <= 1 x 2.5 mm² with or without cable end Screw clamp terminal, <= 2 x 1.5 mm² with or without cable end
Cable Entry	1 plain hole for M20 cable gland 1 plain hole for M16 cable gland
Mechanical Durability	2000000 cycles
[le] Rated Operational Current	3 A, 240 V, AC-15, A300 0.27 A, 250 V, DC-13, Q300 conforming to IEC 60947-5-1 appendix A
[Ui] Rated Insulation Voltage	500 V (pollution degree 3) conforming to IEC 60947-1 500 V (pollution degree 3) conforming to NF C 20-040 group C 500 V (pollution degree 3) conforming to VDE 0110 group C 300 V conforming to UL 508 300 V conforming to CSA C22.2 No 14
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947-1
Maximum Resistance Across Terminals	25 MOhm conforming to IEC 60255-7 category 3 25 MOhm conforming to NF C 93-050 method A
Short-Circuit Protection	10 A cartridge fuse type gG conforming to IEC 60947-5-1 10 A cartridge fuse type gG conforming to VDE 0660-200
Rated Operational Power In W	10 W DC-13, operating rate <60 cyc/mn, 5000000 cycles, 24 V, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 4 W DC-13, operating rate <60 cyc/mn, 5000000 cycles, 120 V, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 7 W DC-13, operating rate <60 cyc/mn, 5000000 cycles, 48 V, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Net Weight	0.295 kg

## **Environment**

Standards	IEC 60947-5-1
Protective Treatment	тн
Ambient Air Temperature For Operation	-2555 °C
Ambient Air Temperature For Storage	-4070 °C
Vibration Resistance	5 gn (f= 10500 Hz) conforming to IEC 60068-2-6
Shock Resistance	25 gn conforming to IEC 60068-2-27
Overvoltage Category	Class II conforming to IEC 61140 Class II conforming to NF C 20-030
Ip Degree Of Protection	IP43 conforming to IEC 60529

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.500 cm
Package 1 Width	12.000 cm
Package 1 Length	18.700 cm
Package 1 Weight	370.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	4
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.738 kg

# Contractual warranty

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations


## **XPEA111**


## **Dimensions Drawings**

## Foot Switch without Trigger Mechanism

#### **Dimensions**

\_mm .kits.





- (1) 1 plain hole for ISO M20 or  $n^{\circ}$  13 (Pg 13.5) cable gland.
- (2) 1 plain hole for ISO M20 or  $n^{\circ}$  9 (Pg 11) cable gland.


#### XPEA111

#### Performance Curves

#### **Electrical Durability of Contacts**

#### **AC-15 Utilization Category**

Operating rate: 3600 operating cycles/hour. Load factor: 0.5. Inductive circuit:



- X Current in A
- Y Millions of operating cycles

#### **DC-13 Utilization Category**

Refer to the product characteristic "Operational power in W".