

XUB9APXNM12

Photoelectric sensors XU, photo electric sensor, cylindrical, plastic, polarised, Smax 7 m, PNP, Connector M12

Main

| | |
|-------------------------------|--|
| Range of product | Telemecanique Photoelectric sensors XU |
| Series name | General purpose single mode |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XUB |
| Sensor design | Cylindrical M18 |
| Detection system | Polarised reflex |
| Material | Plastic |
| Line of sight type | Axial |
| Type of output signal | Discrete |
| Supply circuit type | DC |
| Wiring technique | 4 wires |
| Discrete output type | PNP |
| Discrete output function | 1 NO or 1 NC programmable |
| Electrical connection | 1 male connector M12, 4 pins |
| Emission | Red LED polarised reflex |
| [Sn] nominal sensing distance | 5 m polarised reflex need reflector XUZC50 |

Complementary

| | |
|---------------------------|--|
| Enclosure material | PC/PBT |
| Lens material | PMMA |
| Maximum sensing distance | 7 m polarised reflex |
| Output type | Discrete |
| Status LED | 1 LED (green) for supply on/stability 1 LED (orange) for output state |
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection |
| Supply voltage limits | 10...30 V DC |
| Switching capacity in mA | <= 100 mA (overload and short-circuit protection) |
| Switching frequency | <= 1000 Hz |
| Maximum voltage drop | <2 V (closed state)no-load |
| Current consumption | < 20 mA no load |
| Maximum delay first up | 100 ms |
| Maximum delay response | 0.5 ms |
| Maximum delay recovery | 0.5 ms |
| Setting-up | Sensitivity by potentiometer |
| Diameter | 18 mm |
| Length | 44 mm |
| Net weight | 0.060 kg |

Environment

| | |
|---------------------------------------|--|
| Product certifications | CE[RETURN]cULus[RETURN]UKCA[RETURN]RoHS |
| Ambient air temperature for operation | -30...55 °C |
| Ambient air temperature for storage | -40...70 °C |
| Relative humidity | 35...95 % |
| Immunity to ambient light | 40000 Lux sunlight 10000 lux incandescent light |

| | |
|-------------------------|---|
| Vibration resistance | 7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) for every axis conforming to IEC 60068-2-6 |
| Shock resistance | 30 gn (duration = 11 ms) for every axis conforming to IEC 60068-2-27 |
| IP degree of protection | IP67 conforming to IEC 60529 IP65 conforming to IEC 60529 IP69K conforming to DIN 40050-9 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.8 cm |
| Package 1 Width | 1.6 cm |
| Package 1 Length | 4.4 cm |
| Package 1 Weight | 40 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 48 |
| Package 2 Height | 15 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 2.235 kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 768 |
| Package 3 Height | 70 cm |
| Package 3 Width | 60 cm |
| Package 3 Length | 80 cm |
| Package 3 Weight | 44.26 kg |

Offer Sustainability

| | |
|--|--|
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |
|--|--|

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|