

# XUK9TAH2MM12

Photoelectric sensors XU, photo electric laser sensor, XUK, reflex, Sn 70 m, 2Q 1Qa 3IN, hoisting app



## Main

Range of Product	Telemecanique Photoelectric sensors XU
Series name	Application hoisting
Electronic sensor type	Photo-electric sensor
Sensor name	XUK
Sensor design	Compact 50 x 50
Detection system	Polarised reflex
Material	Plastic
Type of output signal	Analogue + discrete
Supply circuit type	DC
Wiring Technique	8-wire
Discrete output type	PNP or NPN
Discrete output function	1 NO or 1 NC programmable
Analogue output range	4...20 mA
Electrical connection	1 male connector M12, 8 pins
Product Specific Application	Distance measurement on reflector
Emission	Red laser polarised reflex class 1 IEC 60825-1
[Sn] nominal sensing distance	229.7 ft (70 m) polarised reflex need reflector XUZC250

## Complementary

Enclosure Material	ABS/PC
Lens material	PMMA
Maximum sensing distance	229.7 ft (70 m) polarised reflex need reflector XUZC250
Output Type	Solid state Analog
Output function governance	Light or dark programmable
Add on output	With alarm output
Add on input	Test by emission breaking
Status LED	1 LED yellow)output state 1 LED green/yellow)supply on/output state
[Us] rated supply voltage	12...24 V DC reverse polarity protection
Supply voltage limits	10...30 V DC
Switching capacity in mA	<= 100 mA overload and short-circuit protection)
Switching frequency	<= 1.5 kHz
Maximum voltage drop	<2 V closed state)
Current consumption	<= 35 mA no-load
Maximum delay first up	300 ms
Maximum delay response	10 ms
Maximum delay recovery	10 ms
Setting-up	Using teach button or remote teaching
Depth	2.0 in (50 mm)
Height	2.0 in (50 mm)
Width	0.9 in (23 mm)
Product Weight	0.077 lb(US) (0.035 kg)

## Environment

Product Certifications	CE[RETURN]Ecolab[RETURN]cULus
Ambient air temperature for operation	-4.0000000000...122.0000000000 °F (-20...50 °C), UL[RETURN]-22.0000000000...122.0000000000 °F (-30...50 °C)
Ambient Air Temperature for Storage	-22.0000000000...140.0000000000 °F (-30...60 °C)
Vibration resistance	7 gn 10...55 Hz) IEC 60068-2-6
Shock resistance	10 gn 11 ms) IEC 60068-2-27
IP degree of protection	IP67 IEC 60529 IP69K DIN 40050

## Ordering and shipping details

Category	US10DS222481
Discount Schedule	0DS2
GTIN	3389119621038
Returnability	No
Country of origin	DE

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.2 in (3.0 cm)
Package 1 Width	2.4 in (6.0 cm)
Package 1 Length	3.6 in (9.2 cm)
Package 1 Weight	2.05 oz (58.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	28
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	5.9 in (15.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	3.618 lb(US) (1.641 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>


## Contractual warranty

Warranty	18 months
----------	-----------



## Connections and Schema

### Connector Wiring



(1) Auto-detect

1 : + UB (BN : Brown)

2 : Q2 - PNP, NO (WH: White)

3 : -UB (BU: Blue)

4 : Q1 - PNP, NO (BK: Black)

5 : QA - 4...20 mA (GY: Grey)

6 : IN1 - Teach-in (PK: Pink)


7 : IN2 - Teach and activated tandem (VT: Purple)

8 : IN3 - Beam off (OG: Orange)

---

Mounting

---



(1) < 1,5 Nm (13 lb-in)

(2) < 1 Nm (8.85 lb-in)