

# Product data sheet

Specifications



Base mounting unit with cover, Harmony XVM, fixing tube 250mm with bracket, plastic, white, 45mm, without buzzer

XVMC213T

! To be discontinued on: 28 July 2023

! To be discontinued

## Main

Range of product	Harmony XVM
Product or component type	Base unit kit
Kit composition	Bracket 250 mm support tube Base unit Cover
Component name	XVM
Indicator bank base type	Base without buzzer

## Complementary

Mounting diameter	45 mm
Housing colour	White
Connections - terminals	Screw terminals, 1 x 0.325...1 x 1.5 mm <sup>2</sup>
Marking	CE
Net weight	0.298 kg

## Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Product certifications	CCC
Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-10...50 °C
Electrical shock protection class	Class I aluminium tube mounting conforming to IEC 60947-1 Class I aluminium tube mounting conforming to IEC 60947-5-1 Class I aluminium tube mounting conforming to IEC 61140
IP degree of protection	IP40 any position except vertical position conforming to IEC 60529 IP42 vertical position conforming to IEC 60529
Protective treatment	TC

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	5 cm
Package 1 Width	5.5 cm
Package 1 Length	32 cm
Package 1 Weight	292 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.835 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>


## Contractual warranty

Warranty	18 months
----------	-----------

Customer Assembled Tower Light

---

Wiring Diagram



**Indicator bank with buzzer (4 illuminated units max.):**

4: 4th illuminated unit

3: 3rd illuminated unit

2: 2nd illuminated unit

1: 1st illuminated unit

N: Common

B: Buzzer

**Indicator bank without buzzer:**

5: 5th illuminated unit

4: 4th illuminated unit

3: 3rd illuminated unit

2: 2nd illuminated unit

1: 1st illuminated unit

N: Common

**Maximum capacity for wiring through support tube:**

- 6 wires x 1 mm<sup>2</sup>/16 AWG,
- 5 wires x 1.5 mm<sup>2</sup>/14 AWG

**Recommended replacement(s)**