

# XZCPV1164L5

Pre wired connectors XZ, straight female, M12,  
5 pins, cable PVC 5 m



## Main

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Range of product                  | Telemecanique Cabling components |
| Accessory / separate part categor | Cabling accessory                |
| Accessory / separate part type    | Pre-wired connectors             |
| Series name                       | General purpose                  |

## Complementary

|                                |                                       |
|--------------------------------|---------------------------------------|
| Electrical connection          | Straight female connector M12, 5 pins |
| Cable connector fixing         | Screw-on                              |
| Collar material                | Metal                                 |
| Status LED                     | Without                               |
| Cable length                   | 5 m                                   |
| Cable outer diameter           | 5.2 mm                                |
| Cable composition              | 5 x 0.25 mm <sup>2</sup>              |
| Wire insulation material       | PVC                                   |
| [Ue] rated operational voltage | 60 V AC<br>75 V DC                    |
| [In] rated current             | 3 A                                   |
| Contact resistance             | 5000 µOhm                             |
| Minimum insulating resistance  | 1 GΩ                                  |
| Net weight                     | 0.18 kg                               |

## Environment

|                                       |                    |
|---------------------------------------|--------------------|
| IP degree of protection               | IP65<br>IP67       |
| Product certifications                | cULus              |
| Ambient air temperature for operation | -25...80 °C static |
| Ambient air temperature for storage   | -25...80 °C        |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 8.000 cm  |
| Package 1 Width              | 5.000 cm  |
| Package 1 Length             | 15.000 cm |
| Package 1 Weight             | 268.000 g |
| Unit Type of Package 2       | S02       |
| Number of Units in Package 2 | 20        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 5.698 kg  |


## Offer Sustainability

|  |   |
|--|---|
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Dimensions




L : Length of cable

---

## Connections and Schemes

---

### Connectors



BU : Blue

BN : Brown

BK : Black

Y/G : Yellow / Green

BK/ Black / White

WH :