Product datasheet

Specifications





Single contact block, Harmony XB5N XB7N, silver alloy, screw clamp terminal, 1 NC

ZBE102N

Main

| Range of product | Harmony XB5N/XB7N |
|-------------------------------|--|
| product or component type | Contact block with protected terminals |
| Device short name | ZBE |
| Sale per indivisible quantity | 20 |
| Contact block type | Single |

Complementary

| Fixing collar material | Plastic |
|---|--|
| Terminals description ISO n°1 | (11-12)NC |
| net weight | 0.011 kg |
| Contacts type and composition | 1 NC |
| Contact operation | Slow-break |
| Contacts usage | Standard contacts |
| Positive opening | With conforming to IEC 60947-5-1 appendix K |
| Operating travel | 2.6 mm (NC changing electrical state) 4.3 mm (total travel) |
| Operating force | 3.5 N NC changing electrical state |
| Operating torque | 0.14 N.m |
| Torque value | 0.14 N.m |
| Mechanical durability | 5000000 cycles |
| Connections - terminals | Screw clamp terminal, <= 2 x 1.5 mm² with cable end conforming to IEC 60947-1 Screw clamp terminal, >= 1 x 0.22 mm² without cable end conforming to IEC 60947-1 |
| Tightening torque | 0.81.2 N.m conforming to IEC 60947-1 |
| Shape of screw head | Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver |
| Contacts material | Silver alloy (Ag/Ni) |
| Short-circuit protection | 10 A cartridge fuse type gG conforming to IEC 60947-5-1 |
| [Ith] conventional free air thermal current | 10 A conforming to IEC 60947-5-1 |
| [Ui] rated insulation voltage | 600 V (pollution degree 3) conforming to IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-1 |

| [le] rated operational current | 3 A at 240 V, AC-15, A600 conforming to IEC 60947-5-1 6 A at 120 V, AC-15, A600 conforming to IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to IEC 60947-5-1 |
|--------------------------------|--|
| Electrical durability | 1000000 cycles, AC-15, 2 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Electrical reliability | Λ < 10exp(-6) at 5 V, 1 mA in clean environment conforming to IEC 60947-5-4 Λ < 10exp(-8) at 17 V, 5 mA in clean environment conforming to IEC 60947-5-4 |

Environment

| protective treatment | Standard version |
|---------------------------------------|---|
| Ambient air temperature for storage | -4070 °C |
| Ambient air temperature for operation | -2570 °C |
| Standards | IEC 60947-5-4 IEC 60947-1 IEC 60947-5-1 IS 13947-5-1 |
| Product certifications | CE |
| Vibration resistance | 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|--------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.0 cm |
| Package 1 Width | 2.8 cm |
| Package 1 Length | 3.2 cm |
| Package 1 Weight | 11.0 g |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

| Circularity Profile | No need of specific recycling operations |
|--------------------------|---|
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Environmental Disclosure | Product Environmental Profile |
| China Rohs Regulation | China RoHS declaration |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Reach Regulation | REACh Declaration |