



Overload relay, Ir= 0.1 - 0.16 A, 1 N/O, 1 N/C, Direct mounting

**Part no.** ZE-0,16  
014263  
**EL Number** 4130474  
(Norway)

General specifications		
Product name		Eaton Moeller® series ZE Thermal overload relay
Part no.		ZE-0,16
EAN		4015080142638
Product Length/Depth		52 millimetre
Product height		65 millimetre
Product width		45 millimetre
Product weight		0.073 kilogram
Certifications		UL File No.: E29184 IEC/EN 60947-5-1 CSA Class No.: 3211-03 IEC/EN 60947-4-1 UL Category Control No.: NKCR CSA File No.: 012528 UL 508 CE IEC/EN 60947 CSA CSA-C22.2 No. 14 VDE 0660 UL
Product Tradename		ZE
Product Type		Thermal overload relay
Product Sub Type		None
Catalog Notes		Ambient air temperature: Operating range to IEC/EN 60947, PTB: -5°C to +50°C Ambient operating temperature (according to IEC/EN 60947) PTB: -5 °C - +55 °C Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified.
Features & Functions		
Features		Test/off button Reset pushbutton manual/auto Trip-free release Phase-failure sensitivity (according to IEC/EN 60947, VDE 0660 Part 102)
General information		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		50 °C
Ambient operating temperature (enclosed) - min		25 °C
Ambient operating temperature (enclosed) - max		40 °C
Class		CLASS 10 A
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Degree of protection		IP20
Mounting method		Direct mounting Direct attachment
Overload release current setting - min		0.1 A
Overload release current setting - max		0.16 A
Overvoltage category		III
Pollution degree		3
Product category		ZE overload relays for mini contactor relays
Protection		Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)		6000 V AC 4000 V (auxiliary and control circuits)
Shock resistance		10 g, Mechanical, Sinusoidal, Shock duration 10 ms
Suitable for		Branch circuits, (UL/CSA)
Temperature compensation		≤ 0.25 %/K, residual error for T > 40°

			Continuous
<b>Terminal capacities</b>			
Terminal capacity (flexible with ferrule)			1 x (0.5 - 1.5) mm <sup>2</sup> , Main cables 2 x (0.5 - 1.5) mm <sup>2</sup> , Main cables 1 x (0.5 - 1.5) mm <sup>2</sup> , Control circuit cables
Terminal capacity (solid)			1 x (0.75 - 2.5) mm <sup>2</sup> , Main cables 1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables
Terminal capacity (solid/stranded AWG)			18 - 14, Main cables 2 x (18 - 12), Control circuit cables
Stripping length (main cable)			8 mm
Stripping length (control circuit cable)			8 mm
Screw size			M3.5, Terminal screw
Screwdriver size			0.8 x 5.5 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
<b>Electrical rating</b>			
Conventional thermal current I <sub>th</sub> of auxiliary contacts (1-pole, open)			6 A
Rated operational current (I <sub>e</sub> ) at AC-15, 120 V			1.5 A
Rated operational current (I <sub>e</sub> ) at AC-15, 220 V, 230 V, 240 V			1.5 A
Rated operational current (I <sub>e</sub> ) at AC-15, 380 V, 400 V, 415 V			0.7 A
Rated operational current (I <sub>e</sub> ) at AC-15, 500 V			0.5 A
Rated operational current (I <sub>e</sub> ) at DC-13, 110 V			0.4 A
Rated operational current (I <sub>e</sub> ) at DC-13, 220 V, 230 V			0.2 A
Rated operational current (I <sub>e</sub> ) at DC-13, 24 V			0.9 A
Rated operational current (I <sub>e</sub> ) at DC-13, 60 V			0.75 A
Rated operational voltage (U <sub>e</sub> ) - max			690 V
Safe isolation			250 V AC, Between auxiliary contacts, According to EN 61140 300 V AC, Between main circuits, According to EN 61140 300 V AC, Between auxiliary contacts and main contacts, According to EN 61140
Switching capacity (auxiliary contacts, general use)			0.6 A, 600V AC, (UL/CSA) 1.5 A, 240V AC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)			R300, DC operated (UL/CSA) D300, AC operated (UL/CSA)
<b>Short-circuit rating</b>			
Short-circuit current rating (basic rating)			1 A, max. Fuse, SCCR (UL/CSA) 15 A, max. CB, CB for max. 480 V, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA)
Short-circuit protection rating			Max. 4 A gG/gL, Fuse, Auxiliary contacts 0.5 A gG/gL, Fuse, Type "2" coordination 20 A gG/gL, Fuse, Type "1" coordination
<b>Contacts</b>			
Number of auxiliary contacts (change-over contacts)			0
Number of auxiliary contacts (normally closed contacts)			1
Number of auxiliary contacts (normally open contacts)			1
Number of contacts (normally closed contacts)			1
Number of contacts (normally open contacts)			1
<b>Design verification</b>			
Equipment heat dissipation, current-dependent P <sub>vid</sub>			4.8 W
Heat dissipation capacity P <sub>diss</sub>			0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>			1.6 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )			0.16 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Thermal overload relay (EC000106)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Thermal overload relay (ecl@ss13-27-37-15-01 [AKF075019])		
Adjustable current range	A	0.1 - 0.16
Max. rated operation voltage Ue	V	690
Mounting method		Direct attachment
Type of electrical connection of main circuit		Screw connection
Number of auxiliary contacts as normally closed contact		1
Number of auxiliary contacts as normally open contact		1
Number of auxiliary contacts as change-over contact		0
Release class		CLASS 10 A
Reset function input		No
Reset function automatic		Yes
Reset function push-button		Yes